

Aspirador – Suction pump AI-78



Aspirador gástrico intermitente modelo AI-78

Gastric-Intermittent suction pump mod.AI-78



Conectores rápidos y válvula de seguridad
Connectors and safety valve

Aspirador para drenaje gástrico, de aspiración continuo/intermitente, con selector de vacío prefijado a 90/120 mmHg y mandos reguladores de los ciclos de paro y puesta en marcha. El aspirador modelo AI-78, dispone de un sistema de aspiración completamente silencioso y libre de engrases, siendo estos factores óptimos para la utilización en UVI, UCI y salas.

Surgical aspirator for digestive drainage, intermittent or continuous, with prefixed vacuum selector to 90/120 mmHg. and regulators controls for the start/stop cycles. The aspirator model AI-78 has an extremely quiet aspiration system which requires no lubrication. These factors are optimum for the utilization of this equipment in UVI, UCI and rooms.

CARACTERÍSTICAS TÉCNICAS

Chasis:	Metálico, pintado al fuego
Motobomba:	De diafragma, sin engrase
Bomba:	Caudal 500 l/h (8.3 l/min)
Vacío :	Prefijado a 90/120 mmHg (11.99 / 15.99 kPa)
Programación:	Continuo / intermitente
ciclo marcha:	De 1 a 120 segundos
ciclo paro:	De 1 a 90 segundos
Frasco recolector:	Dos frascos de policarbonato de 3 litros
Tensión eléctrica:	230 V/ 50 Hz (otros bajo demanda)
Potencia:	18 VA
Medidas:	38 X 25 X 86 cm
Peso:	12 Kg aproximado
Normativa:	UNE EN 60601 / EN 61000 / UNE EN 10079

RECAMBIOS OPCIONALES

FB-193A	Filtro bactericida (10/50 unidades)
FV010018	Frasco recolector de 3 litros (2 unidades)
FV010300	Frasco recolector de 3 litros, con tapón y conectores.

TECHICAL DATA

Chassis:	Metallic, fire painted
Engine pump:	With membrane, no lubrication
Pump:	Flow 500 l/h (8.3 l/min)
Vacuum:	Prefixed 90 / 120 mmHg (11.99 / 15.99 kPa)
Programme:	Continuous / intermittent
Start cycle:	From 1 to 120 seconds
Stop cycle:	From 1 to 90 seconds
Collecting flask:	Two flasks of 3 litres in polycarbonate
Voltage:	230 V / 50 Hz (under request)
Power:	18 VA
Sizes:	38 X 25 X 86 cm
Weight:	12 Kg approximate
Norms:	UNE EN 60601 / EN 61.000 / UNE EN ISO 10079

OPTIONAL SPARES

FB-193A	Bacteria filter (10/50 units)
FV010018	Collecting flask of 3 litres (2 units)
FV010300	Collecting flask of 3 litres, with top and connectors



Panel de mandos con selector de continuos intermitentes
Control panel with continuous or intermittent selector



Asa de transporte, sujeta cables y tubos
Transport handle, cables and tubes hold up



Filtro Bactericida
Bactericide filter

Reg. AI-78 SP-EN/003



Tecnología, 2, nau 7
08780, PALLEJA (Barcelona), SPAIN
Tel.: (+34) 93 334 01 12 - Fax: (+34) 93 440 25 64
www.ordisi.com - comercial@ordisi.com - export@ordisi.com

