

DATA SHEET L21-25R

LAMPARA DE RECONOCIMIENTO RODABLE A LED SERIE L21-25
Moveable lamp of recognition L21-25 LED series

| CARACTERÍSTICAS TÉCNICAS | | TECHNICAL CHARACTERISTICS |
|---|--|--|
| Fuente de luz | LED | Light Source |
| Temperatura de color | 5000 °K | Colour temperature |
| CRI (Ra) | > 96 | CRI (Ra) |
| Intensidad lumínica | 1m - 50.000 lux 0,5m - 87.000 lux | Luminous intensity |
| Vida media LEDs | 60.000 h | Average LEDs Lifetime |
| Regulación de intensidad | Opcional / Optional | Brightness control |
| Diámetro campo a 1 m d ₅₀ | Ø 200 mm | Light field diameter at 1m d ₅₀ |
| Diámetro campo a 1 m d ₁₀ | Ø 400 mm | Light field diameter at 1m d ₁₀ |
| Profundidad de iluminación (L1+L2) al 60% | 87 cm | Depth of illumination (L1+L2) at 60% |
| Voltaje | 100-240 V 47-63 Hz | Voltage |
| Potencia | 112 VA / 50 W | Power consumption |
| Número de LEDs | 15 | Number of LEDs |
| Montaje | Base rodable de 4 ruedas (2 con freno)* 4 castor stand (2 with brakes)* | Configuration |
| Peso bruto / neto | 16kg / 12,5kg | Gross / net weight |
| Dimensión de embalaje | 131 x 45 x 24cm | Packing size |
| Normas aplicadas | EN60601-1, EN60601-2-41, EN60601-1-2, ISO 14971, ISO 13485, ISO 9001 | Applied standards |

* Posibilidad de montar ruedas antiestáticas / Antistatic castors available

DIMENSIONES / DIMENSIONS

